



**Specifications Ledvance LED  
Downlight Performance DN155 14W  
1600lm 65D - 840 Cool White | 180mm  
- IP54 - Dali Dimmable**

[View Product](#)

## General Information

|                      |                                    |
|----------------------|------------------------------------|
| SKU                  | 238967                             |
| EAN                  | 4058075459311                      |
| Manufacturer Code    | 4058075459311                      |
| Brand                | Ledvance                           |
| Manufacturer Name    | DL UGR19 DN155 PFM 14W/840 DALI WT |
| Budgetlight warranty | 5 Years                            |
| Average Lifetime (h) | 70000                              |

## Technical Information

|                             |                 |
|-----------------------------|-----------------|
| Emergency Lighting          | No              |
| Tiltable                    | No              |
| Technology                  | LED Integrated  |
| Wattage                     | 14W             |
| Voltage (V)                 | 220-240         |
| Dimmable                    | Dimmable        |
| Colour Code                 | 840 Cool White  |
| Colour temperature (Kelvin) | 4000 Cool White |
| Colour Rendering (Ra)       | 80-89           |
| Colour of Light             | White           |
| Light Colour Options        | Single Color    |

|                         |                    |
|-------------------------|--------------------|
| Inclusief Driver        | Yes                |
| Beam Angle (degree)     | 65                 |
| Luminous Flux (Lumen)   | 1600lm             |
| Lumen per watt          | 115                |
| Powerfactor             | >0.90              |
| Installation Depth (mm) | 100                |
| Unified Glare Rating    | < 19 - For offices |
| Optische Afdekking      | PC (Polycarbonate) |
| Type product            | LED Downlight      |

## Fixture Information

---

|                        |                        |
|------------------------|------------------------|
| Mounting Method        | Recessed               |
| Cut out (mm)           | 155                    |
| IP-rating              | IP54                   |
| Impact Protection (IK) | IK03 - 0.35 joule      |
| Bedrijfstemperatuur    | -20 to +45             |
| Housing                | Aluminium              |
| Colour of the Fixture  | White                  |
| Colour of material     | White                  |
| Fixture Connection     | Screw terminal, 5-pole |
| Product Serie          | DN155                  |

## Dimensions

---

|               |     |
|---------------|-----|
| Height (mm)   | 65  |
| Diameter (mm) | 180 |

## Sensor Information

---

Type of sensor

No Sensor

## Why Budgetlight?



Guaranteed **budget prices**



Up to **7 years warranty**



**Easy** return process



Long-life **LED solutions**