


## Specifications Noxion LED Downlight Apollo V2.0 9W 1120lm - 830/840 CCT | 145mm - Cutout 120mm



[View Product](#)

### General Information

|                      |                                                                            |
|----------------------|----------------------------------------------------------------------------|
| SKU                  | 256981                                                                     |
| EAN                  | 8719157068574                                                              |
| Manufacturer Code    | 8719157068574                                                              |
| Brand                | Noxion                                                                     |
| Manufacturer Name    | Noxion LED Downlight Apollo V2.0 9W 1120lm 2CCT Cutout Ø120mm Frame Ø145mm |
| Budgetlight warranty | 6 Years                                                                    |
| Average Lifetime (h) | 100000                                                                     |

### Technical Information

|                             |                                  |
|-----------------------------|----------------------------------|
| Tiltable                    | No                               |
| Technology                  | LED Integrated                   |
| Replaces (Watt)             | 24                               |
| Wattage                     | 9W                               |
| Voltage (V)                 | 220-240                          |
| Dimmable                    | Not Dimmable                     |
| Colour Code                 | 830 Warm White, 840 Cool White   |
| Colour temperature (Kelvin) | 3000 Warm White, 4000 Cool White |
| Colour Rendering (Ra)       | 80-89                            |
| Colour of Light             | White                            |
| Light Colour Options        | CCT                              |

|                       |                    |
|-----------------------|--------------------|
| Beam Angle (degree)   | 60                 |
| Luminous Flux (Lumen) | 1120lm             |
| Lumen per watt        | 130                |
| Powerfactor           | >0.90              |
| Unified Glare Rating  | < 19 - For offices |
| Optische Afdekking    | PC (Polycarbonate) |
| Afwerking Reflector   | White              |
| Type product          | LED Downlight      |

## Fixture Information

|                        |                               |
|------------------------|-------------------------------|
| Mounting Method        | Recessed                      |
| Cut out (mm)           | 120                           |
| IP-rating              | IP20                          |
| Impact Protection (IK) | IK02 - 0.20 joule             |
| Bedrijfstemperatuur    | -20 to +40                    |
| Housing                | Aluminium                     |
| Colour of the Fixture  | White                         |
| Fixture Connection     | PI [Push-in connector 2-pole] |
| Product Serie          | Apollo                        |

## Dimensions

|               |     |
|---------------|-----|
| Height (mm)   | 92  |
| Diameter (mm) | 145 |

**Sensor Information**  Guaranteed **budget prices**  Up to **7 years warranty**

Type of sensor  **Easy** return process  No Sensor  Long-life **LED solutions**